**POLAR-E 7.5-10-500 ES**

# Screw compressor with direct drive transmission, complete with tank and dryer.

Lubricated screw compressor with coaxial transmission. LOGIN electronic controller. Compact and silent, with dryer mounted on 500-litre tank




## Technical data

| | | |
|---|---|---|
| Product code | | V83LR92N1NB55 |
| Lubrication | | Lubricated |
| Air-end | | FS26 |
| Air receiver (l) | | 500 |
| Power | | 7.5 |
| Air outflow | l/min. | 950 |
| | m3/min. | 0,95 |
| | c.f.m. | 33 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | | 1 |
| Sound level (dB(A)) | | 62 |
| Voltage / Frequency (Volt / Hz) | | 400/50 |
| Connection (G) | | 1" |
| Controller | | LOGIN MINI |
| Type motor | | Electric |
| Energy efficiency | | IE3 |
| Gross weight (kg) | | 365 |
| Net weight (kg) | | 325 |
| Packaging dimensions LxWxH (mm) | | 2070x800x1850 |
| Net Dimensions LxWxH (mm) | | 1970x680x1580 |

*Sound pressure level measurement carried out at a distance of 4 metres.