**SIRIO-E 15-10-500**

# Screw compressor with belt transmission, complete with tank.

Three-phase belt-transmission lubricated screw compressor with LOGIN electronic controller and star/delta starterer. Soundproof cab made of painted sheet metal and complete with 500-litre tank




## Technical data

| | | |
|---|---|---|
| Product code | | V83EN92N1NA55 |
| Lubrication | | Lubricated |
| Air-end | | FS26 |
| Air receiver (l) | | 500 |
| Power | | 15 |
| Air outflow | l/min. | 1900 |
| | m3/min. | 1,9 |
| | c.f.m. | 67 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | | 1 |
| Sound level (dB(A)) | | 68 |
| Voltage / Frequency (Volt / Hz) | | 400/50 |
| Connection (G) | | 3/4" |
| Controller | | LOGIN MINI |
| Type motor | | Electric |
| Energy efficiency | | IE3 |
| Gross weight (kg) | | 395 |
| Net weight (kg) | | 355 |
| Packaging dimensions LxWxH (mm) | | 2070x800x1850 |
| Net Dimensions LxWxH (mm) | | 1950x680x1580 |

*Sound pressure level measurement carried out at a distance of 4 metres.